BYD SEAL U SUPER HYBRID

1. 10 years free cloud service from first activation, 1.0 GB entertainment data per month for free in first 2 years from first activation.

* Apple CarPlay is a trademark of Apple Inc., registered in the U.S. and other countries. Please check Apple CarPlay's available regions at www.apple.com/ios/feature-availability/#apple-carplay * Android and Android Auto are trademarks of Google LLC. Please check Android Auto's available regions at g.co/androidauto/requirements.

* To wirelessly use Android Auto any car display, you need a compatible Android smartphone with an active data plan. You can check which smartphones are compatible at g.co/androidauto/requirements.
* To use Android Auto on your car display, you'll need an Android phone running Android 8 or higher, an active data plan, and the Android Auto app.compatible at g.co/androidauto/requirements.

Safety	Boost	Comfort	Design
Driver's airbag	•	•	•
Front passenger's airbag, deactivation switch	٠	٠	•
Front centre airbag	٠	٠	•
Front side airbags	•	•	•
Side curtain airbags	•	•	•
Pre-tensioned & force limiter front seat belts	•	•	•
Pre-tensioned outer rear seats belts	٠	٠	•
Rear middle seat force limiting seat belt	•	•	•
ISOFIX and i-Size, front passenger and outer rear seats	•	•	•
Tyre Pressure Monitoring System (TPMS)	•	•	•
Child Presence Detection (CPD)	•	•	•
Anti-theft system	•	•	•
Auto-lock system	۲	•	•
Mechanical child safety lock	•	•	•
Emergency call	۲	•	•

Driving Assistance	Boost	Comfort	Design
Parking radars, front and rear	•	•	٠
360° view camera	•	•	•
Adaptive Cruise Control (ACC) & Intelligent Cruise Control (ICC)	•	•	•
Lane Keep Assistance (LKA)	•	•	•
Blind Spot Detection (BSD)	•	•	•
Indirect Driver Fatigue Management (DFM)	•	•	•
Traction Control System (TCS)	•	•	•
Lane Change Assist (LCA)	•	•	•
Electronic Brake Distribution (EBD)	•	•	•
Intelligent Speed Limit Control (ISLC)	•	•	•
Front Cross Traffic Alert (FCTA) & Front Cross Traffic Brake (FCTB)	•	•	•
Rear Cross Traffic Alert (RCTA) & Rear Cross Traffic Brake (RCTB)	•	•	•
Emergency Lane Keeping Assist (ELKA)	•	•	•
Predictive Collision Warning (PCW)	•	•	•
Forward Collision Warning (FCW)	•	•	•
Rear Collision Warning (RCW)	•	•	•
Lane Departure Warning (LDW)	•	•	•
Door Opening Warning (DOW)	•	•	•
Lane Departure Assistant (LDA)	•	•	•
Electric Parking Brake (EPB)	•	•	•
Comfort Stop (CST)	•	•	•
Lane Departure Prevention (LDP)	•	•	•
Hill Decent Control (HDC)	•	•	•
Auto Hold	•	•	•
Automatic Emergency Braking (AEB)	•	•	•
Traffic Sign Recognition (TSR)	•	•	•
Hydraulic Brake Assistant (HBA)	•	•	•
Hydraulic Boost Brake (HBB)	•	•	•
Controller Deceleration Parking (CDP)	•	•	•
Vehicle Dynamics Control (VDC)	•	•	•
Hill Hold Control (HHC)	•	٠	•
Rollover Control System (RMI)	•	•	•
Brake Override System (BOS)	•	•	•

Convenience & Efficiency	Boost	Comfort	Design
Vehicle-to-Load (V2L) function	٠	•	٠
Driving modes: Eco, Normal, Sport, Snow	٠	•	
Driving modes: Eco, Normal, Sport, Snow, Sand, Muddy			•
2 x Smart key	٠	•	•
Keyless entry & Keyless start	•	•	•
11kW On-Board Charger (OBC)	•	•	٠

Paint Colour Options			Boost	Comfort	Design
Obsidian Black			•	•	٠
Time grey			•	•	٠
Snow white			•	•	•
Sky blue			٠	•	•
				-	
Obsidian Black	Time grey	Snow white		Sky blue	

Interior Colour Options	Boost	Comfort	Design	
Black	•	•	٠	



Black

Technical Data

Vehicle Weight & Capacity	Boost	Comfort	Design
Kerb weight (kg)	1940	1995	2100
Gross vehicle weight (kg)	2350	2405	2510
Max. front axle load (kg)	1230	1259	1275
Max. rear axle load (kg)	1140	1166	1255
Max. roof load (kg)	75	75	75
Min. turning circle (m)	5.5	5.5	5.5
Boot volume (L)	425	425	425
Boot volume - seats down (L)	1440	1440	1440

Dimensions (mm)	Boost	Comfort	Design
Length	4775	4775	4775
Width	1890	1890	1890
Width with extended exterior mirror	2085	2085	2085
Height	1670	1670	1670
Wheelbase	2765	2765	2765
Front track	1630	1630	1630
Rear track	1630	1630	1630



* All information and illustrations are based on data available at the time of print and are subject to change without prior notice. Please contact your local BYD dealer for the latest information.

Technical Data

Power performance	Boost	Comfort	Design
System total max power (kW/PS)	160/217	160/217	238/323
System total max torque (N·m/Ib ft)	300/221	300/221	550/405
Engine max net power (kW/HP)	72/96	72/96	96/128
Rev. at max power (rpm)	6000	6000	5200
Engine max torque (N•m/lb ft)	122/89	122/89	220/162
Rev. at max torque (rpm)	4000-4500	4000-4500	1500-3500
Electrical motor max power (kW/PS)	145/197	145/197	Front: 150/203 Rear: 120/16
Electrical motor max torque (N•m/Ib ft)	300/221	300/221	Front: 300/221 Rear: 250/18
Engine & Transmission	Boost	Comfort	Design
Displacement	1498 cc/1.5 L	1498 cc/1.5 L	1497 cc/1.5 T
Cylinder	4	4	4
Transmission	Automatic	Automatic	Automatic
Battery	Boost	Comfort	Design
Battery type		BYD Blade Battery (LF	FP)
Battery capacity (kWh)	18.3	26.6	18.3
Nominal voltage (V)	339.2	339.2	339.2
CO ₂ Emissions	Boost	Comfort	Design
CO ₂ Emissions-combined (g/mile)	26	15	37
Emission standard	Euro 6e	Euro 6e	Euro 6e
Tank volume (gallons)	13.2	13.2	13.2
Fuel type	Petrol	Petrol	Petrol
Fuel grade, minimum	95 E10	95 E10	95 E10
WLTP Range & Consumption ^{2,3}	Boost	Comfort	Design
.	80	124	70
Electric range - combined (km)	110	168	98
Electric range - city (km)			
Range - combined (km) Electric consumption - combined (km/kWh)	1073	1120	864
	5.9	5.6	5.0
Electric consumption - city (km/kWh) Fuel Consumption - low (mpg)	6.9	6.9	5.6
Fuel Consumption - medium (mpg)	61.5	78.5	47.1
Fuel Consumption - high (mpg)	58.9	52.4	52.4
Fuel Consumption - combined (mpg)	58.9	55.4	45.6
Fuel Consumption - weighted combined (mpg)	51.4	50.5	41
r der consumption - weighted combined (mpg)	403.9	706.8	282.7
Charging Time 4,5	Boost	Comfort	Design
Charging port	CCS2	CCS2	CCS2
Max AC charging power	11 kW	11 kW	11 kW
AC charging time (11kW 3-phase) 15%-100%	120 min	192 min	120 min
Max DC charging power	18 kW	18 kW	18 kW
DC charging time SOC 30%-80%	35 min	55 min	35 min
Driving Performance	Boost	Comfort	Design
Electric motor type	Permanent Magne	t Synchronous Motor	Front: Permanent Magnet Rear: Synchronous Motor
Drive mode	FWD	FWD	AWD
Acceleration 0-100km (s)	8.9	8.9	5.9
Top speed (km/h)	169	169	180
Drag coefficient (Cd)	0.34	0.34	0.34
Front suspension	MacPherson	MacPherson	MacPherson
Rear suspension	Multi-Link	Multi-Link	Multi-Link
Brakes	Front Ventilated Disc Brakes		
2. Power consumption is calculated in accordance with Regulation (EU) 2017-1151.		Rear Disc Brakes	

The WLTP range and consumption values are obtained under standard EU test conditions, according to the uniform provisions concerning the approval of motor vehicles with regard to the emissions based on the new World Harmonized Light Vehicle Test Procedure (WLTP). The actual range and energy consumption figures may vary due to a number of factors such as weather conditions, traffic situation, vehicle load and driving behaviours.

4. Charging times and charging speed may vary due to different factors such as battery temperature, specs of charging infrastructure, state of charge. A CCS2 DC charger with the output higher than 100kW and the voltage higher than 500V, as well as the suitable ambient temperature (25°C) are required to achieve the maximum charging speed.

5. The AC charging power can up to 11kW while the actual charging power might be limited at low SOC.